

Basic KSL for TLDS, TLDS+, TLDP, TLM, TL (TLK only in exceptions)	Änderungen (Historie): : Positionen «offer» angepasst	Blatt Nr: 1	Blatt Anzahl: 2		A4
		gezeichnet	06.02.2019	ER	Zeichn.-Typ
Für dieses Dokument behalten wir uns alle Rechte vor. Ohne unsere ausdrückliche und schriftliche Zustimmung darf es weder dritten Personen mitgeteilt, noch missbräuchlich kopiert oder anderweitig benutzt werden. VOR_02_Form-A4.E, FC 111003ER LM 130828ER Printdate 29.03.2019		geändert	29.03.2019	ER	BGZ
		geprüft	29.03.2019	KL	INDEX
		freigegeben	23.03..2019	ER	B
AirWork & Heliseilerei GmbH (A&H) Your Partner. In Safety! A&H Engineering Bahnhofweg 1 CH-6405 Immensee					
DB Ropes-manual_KSL_B					MS n/a

Offer positions and details (part number, WLL, size, length, colour)

Type of helicopter: _____, WLL _____, Customer (KZK): _____, AD: _____

10, your choice or **10** our offer


Offer pos. ___
DB Special fittings

Offer pos. ___
DB Damper
A&H_SB-2013-1 Damper

Offer pos. ___
DB SL-LL

Offer pos. ___
DB SLE1

Offer pos. ___ options



P/N:	WLL 10	14	20	30	40	50	60	76	90 kN
AW	13	13							
AM_KAU_	H135-M	H135-M	H145-M	i)	MIL	MIL	MIL	i)	i)

- > i) on request. Please tell us your type of primary cargo hook with dimensions!
- > _____

VM-DP_	10	14	20	30	40	50	60	--	--_1.5
VM-DP_	--	14	20	30	40	50	60	--	--_1.5L

- > 1.5 means the standard length, L means «for Logging» (HESLO 3)
- > All dampers are equipped with protective sheath and standard fittings Grade 10, other fittings on request

Example: TLM_14_50_Y (WLL 14 kN, length 50 m, colour yellow)

TLDS_	10	--	20	30	40	50	--	--	--
TLDS+_	--	14	--	--	--	--	--	--	--
TLDP_	10	14	--	--	--	--	--	--	--
TLM_	10	14	20	30	40	50	60	76	90
TL_	10	14	20	30	40	50	60	76	90
(TLK)_	10	14	20	30	--	--	--	--	--

Select type and then length with color per each. Colour codes: red (R), yellow (Y), blue (B), green (G), grey (GR), black (BK)

- > _____
- > _____
- > _____
- > oblong ring in the upper thimble assy: YES NO
- > lines longer than 50 m and/or other WLL on request

Alle fittings (connex and safety hooks) in Grade 10
Strong thimble in V4A inox steel

SLE1_	10	15	20	30	40	50	ii)	ii)	ii)	kg/pe
Grad 8	1.4	2.9	5.8	10	15.0	15.0				

- > select by size (WLL) or mass (kg)
- > ii) bigger one on request and additional mass on request
- > more information see on AWA_SLE1_T4
- > other types (SLE2 oder SLE3) on request

Basic KSL for TLDS, TLDS+, TLDP, TLM, TL (TLK only in exceptions)	Änderungen (Historie): : Positionen «offer» angepasst	Blatt Nr: 2	Blatt Anzahl: 2		A4
		gezeichnet	06.02.2019	ER	Zeichn.-Typ
Für dieses Dokument behalten wir uns alle Rechte vor. Ohne unsere ausdrückliche und schriftliche Zustimmung darf es weder dritten Personen mitgeteilt, noch missbräuchlich kopiert oder anderweitig benutzt werden. VOR_02_Form-A4.E, FC 111003ER LM 130828ER Printdate 29.03.2019	Your Partner. In Safety!	geändert	29.03.2019	ER	BGZ
		geprüft	29.03.2019	KL	INDEX
		freigegeben	23.03..2019	ER	B
AirWork & Heliseilerei GmbH (A&H) A&H Engineering Bahnhofweg 1 CH-6405 Immensee		DB Ropes-manual_KSL_B			MS n/a